TRANSMITTAL OF SHOP DRAWINGS, EQUIPMENT DATE, MATERIAL SAMPLES, OR  MANUFACTURE'S CERTIFICATES OF COMPLIANCE  (Read instructions on the reverse side prior initiating this form)  SECTION 1-REQUEST FOR APPROVAL OF THE FOLLOWING IT				DATE	NO. 13.00 31-2.5					
TO:	SECTION 1-REQUEST	FROM:	GITEMS (This section	CONTRACT		or)	CHECK ONE	_		
K-C PMC		SAMSUNG CONSOR	TIUM		1009556 ☐ THIS IS A NEW TRANSMI ☐ THIS IS A RESUBMITTAL 0 TRANSMITTAL 08 11 13.00			UBMITTAL OF	OF	
SPECIFIC	CATION SEC.NO.(Cover only one section with each	PROJECT TITLE AND LOCATION	CY08 YRP PN A08Y	901, HIGH	SCHOOL		CHECK ONE:THIS	TRANSMITTAL	. IS	
transmitte	al) 08 11 13.00 31		USAG HUMPHREY	S, KOREA			FOR D FIO 🗵	GOV'T. APPRO	VAL	
NO.		OF ITEM SUBMITTED  del number/etc.)	MFG OR CONTR, CAT.,CURVE DRAWING OR BROCHURE NO. (See instruction no.8)	NO OF COPIES	DOC SPEC PARA NO.	T REFERENCE UMENT DRAWING SHEET NO.	FOR CONTRCTOR USE CODE	VARIATION (See instruction No.6)	FOR CE USE CODE	
15	a. TYPE-F, INSULATED STL HOLLOW CORE V/GLASS 150*800	W/STL FRAME, 900*2100*45, STC-44,	Product Data	d. 3	e. 2.1/2.7	AE611, AE621~AE634	g. "A"	h.	A	
	44 STC RATING #14GA, Level III, Heavy Duty, Sound Inst	lation Materials				AE641, AE642			, ,	
	Polyurethane Foam, Mechanically Interlocked, Hemmed Ve	rtical Edge Seam, Full Flush Design								
	#14GA. Steal Frame Knocked Down Unit, Concrete Wall To	rpe 4-Existing Opening Anchor Per Each Jamb								
	Hot-Dipped Galvanized Steel, Conforming To KS D 3506, S	lim Trim Vision Kit for 150mm x 800mm Visible	Size,	CP						
	Insulated Glass; ANNEALED 6mm + AIR SPACE 12mm +	LAMINATED (2007) AUSTRIA 2003 3mm			(0)			100		
	Frame Size, 44mm Face & 152mm Depth w/15mm B	ackbend No.	1/	RECEI	VED					
	R.Opening Size; 1000mmW x 2150mmH, Door Size;	900mm 1000mg 1 825mm HK	2	013. 02.	07 )					
	MFR: Samhoon Co., Ltd.	명박조고교	10	No.	0					
	POU: Door No.:D31, D120, D154, D168, D188, D	227, D243 <b>6</b> 为		• .	1					
REMARK	S	S S V			in detail and are c	KIM, KWA	onformance with the except as other wise		2	
		SECTION II-APPROVAL ACTIO	N							
	URES RETURNED(List by Item No.)  ORM 4025-R.MAR 95	NAME, TITLE AND SIGNA	Mrsan(	h	SHEET 1 OF	2_	18 F	el Z	13	

× . . . .

TRANSMITTAL OF SHOP DRAWINGS, EQUIPMENT DATE, MATERIAL SAMPLES, OR MANUFACTURE'S CERTIFICATES OF COMPLIANCE				DATE	7 <b>含</b> . Feb. 201	3	FRANSMITTAL NO. 08 11 13.00 31-2.5		
	* PALLACON AREA SCALE LIMITATION OF THE PARTY OF THE PART	everse side prior initiating this form)			•				
TO: K-C PMC FROM:				will be initiate CONTRACT		r)	CHECK ONE  THIS IS A NEW TRANSMITTAL  THIS IS A RESUBMITTAL OF		
SPECIFI transmitt	CATION SEC.NO.(Cover only one section with each	PROJECT TITLE AND LOCATION	CY08 YRP PN A08Y USAG HUMPHREY		SCHOOL		TRANSMITTAL CHECK ONE:THIS FOR D FIO SI	TRANSMITTA	LIS
ITEM NO.	DESCRIPTION	N OF ITEM SUBMITTED model number/etc.)	MFG OR CONTR, CAT, CURVE DRAWING OR BROCHURE NO. (See instruction no.8)	NO OF COPIES		REFERENCE IMENT DRAWING SHEET NO.	FOR CONTRCTOR USE CODE	VARIATION (See instruction No.6)	FOR CE USE CODE
a.	b. TYPE-F, INSULATED STL HOLLOW CORE V/GLASS 150*800 & SMOKE RESISTANCE	E W/STL FRAME, 900*2100*45, STC-35,	c. Product Data	d. 3	e. 2.1/2.7	AE611, AE621~AE634	g. "A"	h.	A
	35 STC RATING #14GA, Level III, Heavy Duty, Sound In	sulation Materials				AE641, AE642			, ,
	Polyurethane Foam, Mechanically Interlocked, Hemmed V	fertical Edge Seam, Full Flush Design							
	#14GA. Steal Frame Knocked Down Unit, Block Out Smo	oke-Rubber Gasket Seal							
	Concrete Wall Type 4-Existing Opening Anchor Per Each	Jamb, Hot-Dipped Galvanized Steel							
	Conforming To KS D 3506, Slim Trim Vision Kit for 150r	mm x 800mm Visible Size, Laminated Glass; 6mm	PVB 0.76+6mm		KCPA	10,1			
	Frame Size:44mm Face & 152mm Depth w/15mm I	Backbend		IA	RECEIVE	0			
	R.Opening Size, 1000mmW x 2150mmH, Door Size	e. 900mmW x 2100mmH x 45mmTHK			2013. 02. 0				
	MFR: Samhoon Co., Ltd.			10	No.	10			
	POU: Door No.:D163a			0		(0)			
REMAR	KS		EDI		in detail and are c	orrect and in strict c	s have been reviewed onformance with the except as other wise		
			EM 185		CQCSM		NGNAM SNATURE OF CON	TRACT	
		SECTION II-APPROVAL ACTIO	)N			NAME AND SIG	SIN TURE OF CON	ITAUT	
ENCLO	SURES RETURNED(List by Item No.)		ATURE OF APPROVING A	UTHORITY			DATE		
		GN	, Mort	lsk	Lea		18 E	eh 20	13
ENG F	ORM 4025-R MAR 95	(ED415 1 10) EDITION OF SER 93 IS (	DRSOLETE		SHEET 2 OF	6	(P	roponent:CEMF	P-CE)

44 - 1 - 4 - 40

## TRANSMITTAL OF SHOP DRAWINGS, EQUIPMENT DATE, MATERIAL SAMPLES, OR DATE TRANSMITTAL NO. MANUFACTURE'S CERTIFICATES OF COMPLIANCE ☐ E. Feb. 2013 08 11 13.00 31-2.5 (Read instructions on the reverse side prior initiating this form) SECTION 1-REQUEST FOR APPROVAL OF THE FOLLOWING ITEMS (This section will be initiated by the contractor) TO: FROM: CONTRACT NO: CHECK ONE K-C PMC SAMSUNG CONSORTIUM 1009556 ☐ THIS IS A NEW TRANSMITTAL IX THIS IS A RESUBMITTAL OF TRANSMITTAL 08 11 13.00 31-2.4 CHECK ONE: THIS TRANSMITTAL IS CY08 YRP PN A08Y901, HIGH SCHOOL SPECIFICATION SEC.NO.(Cover only one section with each PROJECT TITLE AND LOCATION transmittal) FOR D FIO S GOV'T. APPROVAL 08 11 13:00 31 USAG HUMPHREYS, KOREA ITEM DESCRIPTION OF ITEM SUBMITTED CONTRACT REFERENCE FOR VARIATION FOR MFG OR CONTR. NO DOCUMENT CONTRCTOR CE NO. CAT., CURVE (See (Type size, model number/etc.) DRAWING OR COPIES SPEC DRAWING USE CODE instruction USE BROCHURE NO. PARA NO. SHEET NO. No.6) CODE (See instruction no.8) d. h. TYPE-F, INSULATED STL HOLLOW CORE W/STL FRAME, 900\*2100\*45, V/GLASS AE611. 17 3 2.1/2.7 "A" Product Data 150\*800 AE621~AE634 Thermal Insulated, Level II, Heavy Duty, Formed-Place Lock Wool AE641, AE642 Impact And Thermal Resistance, Mechanically Interlocked, Hemmed Vertical Edge Seam, Full Flush Design Frame#16GA. Door#21GA. Steal Frame Knocked Down Unit, Concrete Wall Type 4-Existing Opening Anchor Per Each Jamb KC. Hot-Dipped Galvanized Steel, Conforming To KS D 3506 Insulated Glass: ANNEALED 6mm + AIR SPACE 12mm + LAMINATED(3mm + PVB 0.76 x 2PLY + 3mm) RECEIVED Frame Size 44mm Face & 152mm Depth w/15mm Backbend, Slim Trim Vision Kit for 150mm x 800mm Visible Size R Opening Size; 1000mmW x 2150mmH, Door Size: 900mmW x 2100mmH x 45mmTHK 0 Na MFR: Samboon Co., Ltd. 0 C POU: Door No.:D155 REMARKS certify that the above submitted items have been reviewed in detail and are correct and in strict conformance with the contract drawings and specifications except as other wise stated. NAME AND SIGNATURE OF CONTRACT SECTION II-APPROVAL ACTION ENCLOSURES RETURNED(List by Item No.) DATE NAME, TITLE AND SIGNATURE OF APPROVING AUTHORITY **ENG FORM 4025-R, MAR 95** (ER415-1-10) EDITION OF SEP 93 IS OBSOLETE SHEET 3 OF 6 (Proponent:CEMP-CE)

27 T. 1 54

TRA	NSMITTAL OF SHOP DRAWINGS, EQUIPMEN	DATE TRANSMITTAL NO.								
	MANUFACTURE'S CERTIF			∏ <b>≅</b> . Feb. 20	13	08 11 13.00 31-2,5				
		everse side prior initiating this form)			1 4.165.20	.5	0.611	15,00 51-2,5		
		FOR APPROVAL OF THE FOLLOWING	GITEMS (This section	will be initiate	ed by the contract	or)				
TO:		FROM:		CONTRACT			CHECK ONE			
	K-C PMC	SAMSUNG CONSORT	TUM		1009556		☐ THIS IS A NE	N TRANSMITT	AL	
							☑ THIS IS A RESUBMITTAL OF			
							TRANSMITTAL	08 11 13,00 3	1-2.4	
SPECIFICATION SEC.NO.(Cover only one section with each		PROJECT TITLE AND LOCATION	CY08 YRP PN A08Y	901, HIGH	SCHOOL		CHECK ONE:THIS	TRANSMITTA	LIS	
transmit	(a) 08 11 13.00 31		USAG HUMPHREY	S, KOREA			FOR □ FIO 図	GOV'T. APPRO	OVAL	
ITEM	DESCRIPTION OF ITEM SUBMITTED		MFG OR CONTR,	NO		CONTRACT REFERENCE		VARIATION	FOR	
NO.	(Type size, rr	nodel number/etc.)	CAT., CURVE DRAWING OR	OF COPIES	SPEC	UMENT DRAWING	CONTRCTOR USE CODE	(See instruction	CE USE	
			BROCHURE NO.	COLLEG	PARA NO.	SHEET NO.	USE CODE	No.6)	CODE	
a.	b.		(See instruction no 8)	d.	е.	f	g.	h.	1	
20	TYPE-C, INSULATED STL HOLLOW CORE E STC-45, V/GLASS 2-150*800	XT DOOR W/STL FRAME, 1900*2100*45,	Product Data	3	2.1/2.7	AE611, AE621~AE634	"A"		A	
	45 STC RATING #14GA, Level III, Heavy Duty, Sound Ins	ulation Materials, Polyurethane Foam				AE641, AE642			( \	
	Mechanically Interlocked, Hemmed Vertical Edge Seam, Fr	ull Flush Design, #14GA. Steal Frame Knocked Dow	n Unit							
-	Hot-Dipped Galvanized Steel, Concrete Wall Type 4-Existing	ng Opening Anchor Per Each Jamb			0.00					
	Conforming To KS D 3506, Slim Trim Vision Kit for 150m	nm x 800mm Visible Size			1 C	Ma				
	Insulated Glass; ANNEALED 6mm + AIR SPACE 12mm	+ LAMINATED(3mm + PVB 0.76 x 2PLY + 3mm)			REC	EIVED				
	Frame Size:44mm Face & 152mm Depth w/15mm Backber	nd			2013. 0	2. 07				
	R.Opening Size, 2000mmW x 2150mmH, Door Size	: 1900mmW x 2100mmH x 45mmTHK		1	No.	0)				
	MFR: Samhoon Co., Ltd.				0	0111				
	POU: Door No.:D43				001					
REMAR	ss <u> </u>	The part of	a posty		in detail and are co	pove submitted items orrect and in strict co and specifications e	onformance with the	d /		
					CQCSM		GNAM L.	TRACT .	1	
		SECTION II-APPROVAL ACTION								
ENCLOS	URES RETURNED(List by Item No.)	NAME, TITLE AND SIGNAT	URE OF APPROVING AL	THORITY	î		DATE			
		CMY	Mood	h	Jee		18 Fe	10 201	3	
ENG F	ORM 4025-R,MAR 95	(ER415-1-10) EDITION OF SEP 93 IS OB:	SOLETE	0	SHEET 4 OF	6	(Pr	oponent CEMP-	CF)	

## TRANSMITTAL OF SHOP DRAWINGS, EQUIPMENT DATE, MATERIAL SAMPLES, OR DATE TRANSMITTAL NO. MANUFACTURE'S CERTIFICATES OF COMPLIANCE ∏ ♣ Feb 2013 08 11 13 00 31-2 5 (Read instructions on the reverse side prior initiating this form) SECTION 1-REQUEST FOR APPROVAL OF THE FOLLOWING ITEMS (This section will be initiated by the contractor) TO: FROM: CONTRACT NO: CHECK ONE K-C PMC SAMSUNG CONSORTIUM 1009556 ☐ THIS IS A NEW TRANSMITTAL I THIS IS A RESUBMITTAL OF TRANSMITTAL 08 11 13.00 31-2.4 SPECIFICATION SEC.NO.(Cover only one section with each PROJECT TITLE AND LOCATION CY08 YRP PN A08Y901, HIGH SCHOOL CHECK ONE: THIS TRANSMITTAL IS transmittab 08 11 13.00 31 USAG HUMPHREYS, KOREA FOR D FIO S GOVT. APPROVAL ITEM DESCRIPTION OF ITEM SUBMITTED MFG OR CONTR. CONTRACT REFERENCE VARIATION FOR NO. (Type size, model number/etc.) CAT., CURVE OF DOCUMENT CONTRCTOR (See CE DRAWING OR COPIES SPEC DRAWING USE CODE instruction USE BROCHURE NO. PARA NO. SHEET NO. No.6) CODE (See instruction no.8) d h. TYPE-C, INSULATED STL HOLLOW CORE EXT DOOR W/STL FRAME, 1700\*2100\*45, 22 AE611. Product Data 3 2.1/2.7 STC-44, V/GLASS 2-150\*800 "A" AE621~AE634 44 STC RATING #14GA, Level III, Heavy Duty, Sound Insulation Materials, Polyurethane Foam AE641, AE642 Mechanically Interlocked, Hemmed Vertical Edge Seam, Full Flush Design, #14GA. Steal Frame Knocked Down Unit Hot-Dipped Galvanized Steel, Concrete Wall Type 4-Existing Opening Anchor Per Each Jamb Conforming To KS D 3506, Slim Trim Vision Kit for 150mm x 800mm Visible Size RECE Insulated Glass; ANNEALED 6mm + AIR SPACE 12mm + LAMINATED(3mm + PVB 0.76 x 2PLY + 3mm) 2013. 07 Frame Size 44mm Face & 152mm Depth w/15mm Backbend R.Opening Size; 1800mmW x 2150mmH, Door Size: 1700mmW x 2100mmH x 45mmTHK ect MFR: Samhoon Co., Ltd. POU: Door No.:D247 REMARKS I certify that the above submitted items have been reviewed in detail and are correct and in strict conformance with the contract drawings and specifications except as other wise stated. COCSM KIM, KWANGNAN NAME AND SIGNATURE OF CONTRACT SECTION II-APPROVAL ACTION ENCLOSURES RETURNED(List by Item No.) NAME, TITLE AND SIGNATURE OF APPROVING AUTHORITY DATE **ENG FORM 4025-R, MAR 95** (ER415-1-10) EDITION OF SEP 93 IS OBSOLETE SHEET\_5\_OF\_6\_ (Proponent:CEMP-CE)

TRANSMITTAL OF SHOP DRAWINGS, EQUIPMENT DATE, MATERIAL SAMPLES, OR  MANUFACTURE'S CERTIFICATES OF COMPLIANCE  (Read instructions on the reverse side prior initiating this form)				DATE TRANSMITTAL NO.  08 11 13.00 31-2.5					
TO:	SECTION 1-REQUEST K-C PMC	FOR APPROVAL OF THE FOLLOWING FROM: SAMSUNG CONSORTI	CONTRACT NO: CHECK ON 1009556 THIS IS				ONE IS IS A NEW TRANSMITTAL S IS A RESUBMITTAL OF		
SPECIFICATION SEC.NO.(Cover only one section with each		PROJECT TITLE AND LOCATION	CY08 YRP PN A08Y	'901, HIGH	SCHOOL		TRANSMITTAL CHECK ONE:THIS	08 11 13.00 31	
transmitt	al) 08 11 13.00 31		USAG HUMPHREY				FOR   FIO   GOVT. APPROVAL		
ITEM NO.		OF ITEM SUBMITTED odel number/etc.)	MFG OR CONTR, CAT., CURVE DRAWING OR BROCHURE NO. (See instruction no.8)	NO OF COPIES		REFERENCE UMENT DRAWING SHEET NO.  f.	FOR CONTRCTOR USE CODE	VARIATION (See instruction No.6)	FOR CE USE CODE
a.	TYPE-C, INSULATED STL HOLLOW CORE EX	XT DOOR W/STL FRAME, 1900*2100*45,	Product Data	3	2.1/2.7	AE611, AE621~AE634	"A"		A
	44 STC RATING #14GA, Level III, Heavy Duty, Sound Inst	ulation Materials, Polyurethane Foam				AE641, AE642			1
	Mechanically Interlocked, Hemmed Vertical Edge Seam, Fu	ill Flush Design, #14GA. Steal Frame Knocked Dowr	Unit						
	Hot-Dipped Galvanized Steel, Concrete Wall Type 4-Existing	ng Opening Anchor Per Each Jamb							
	Conforming To KS D 3506, Slim Trim Vision Kit for 150m	m x 800mm Visible Size			KCP	ME			
	Insulated Glass; ANNEALED 6mm + AIR SPACE 12mm +	+ LAMINATED(3mm + PVB 0.76 x 2PLY + 3mm)		/	RECE	VED \			
	Frame Size:44mm Face & 152mm Depth w/15mm Backber	nd			2013. 02	07			
	R.Opening Size, 2000mmW x 2150mmH, Door Size	; 1900mmW x 2100mmH x 45mmTHK		1	0	0			
	MFR Samhoon Co., Ltd				No.	(i)			
	POU: Door No.:D34,D87, D92, D93, D96, D105,	D126, D131, D159, D209, D212			ect	0			
REMAR	(S		- Los		in detail and are o	orrect and in strict of and specifications of	s have been reviewed onformance with the except as other wise		
						NAME AND SI	GNATURE OF CON	TRACT	
		SECTION II-APPROVAL ACTION							
ENCLO	SURES RETURNED(List by Item No.)	NAME, TITLE AND SIGNAT	URE OF APPROVING A	UTHORITY	Lac		18 Fe	محر ما	13
ENG	ORM 4025-R,MAR 95	(ER415-1-10) EDITION OF SEP 93 IS OB	SOLETE	7	SHEET 6 OF	6_	(F	roponent:CEMP	-CE)